

Philips PAL coax cable

1,5 m Male-Female Right angle

SWV2829W



Ensure a reliable connection

with this Pal type Coaxial Cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

• Nickel-plated connectors for reliable contact

Enjoy good audio quality

• High purity copper conductor for reliable signal transfer

Protects against signal loss

• Bare copper shielding

Easy installation

• Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- · Rubber strain relief



Specifications

Packaging dimensions

- EAN: 87 12581 38052 6
- Number of products included: 1
- Packaging type: Blister
- Packaging dimensions (W x H x D): 9.4 x 23.4 x 3.62 cm
- Nett weight: 0.048 kg
- Gross weight: 0.073 kg
- Tare weight: 0.025 kg

Outer Carton

- EAN: 87 12581 38054 0
- Number of consumer packagings: 12

- Outer carton (L x W x H): $41.5 \times 32.6 \times 10.7$ cm
- Nett weight: 0.576 kg
- · Gross weight: 1.49 kg
- Tare weight: 0.914 kg

Inner Carton

- EAN: 87 12581 38053 3
- Number of consumer packagings: 4
- Inner carton (L x W x H): 39.5 x 10.2 x 8.7 cm
- Nett weight: 0.192 kg
- Gross weight: 0.36 kg
- Tare weight: 0.168 kg

Highlights

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shieldingBare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2014-02-05

© 2014 Koninklijke Philips N.V. All Rights reserved.

Version: 1.0.7

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 000 35472 EAN: 87 12581 38052 6

www.philips.com